

## 1. Product and Company Identification

<b>Product identifier</b>	<b>2 Cycle +</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Lubricant / Oil
<b>Recommended restrictions</b>	None known.
<b>Manufacturer information</b>	Irving Blending & Packaging PO Box 1169 Saint John, NB E2L 4E6 CA Phone: 1.800.574.5823 Emergency Phone: 1.800.424.9300 (CHEMTREC) Emergency Phone: 1.506.648.3060
<b>Supplier</b>	See above.

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Specific target organ toxicity, repeated exposure	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Flammable liquid and vapor. Causes skin irritation. Causes eye irritation. Causes damage to organs through prolonged or repeated exposure.
<b>Precautionary statement</b>	
<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not breathe the mist or vapor. Do not eat, drink or smoke when using this product.
<b>Response</b>	In case of fire: Use appropriate media to extinguish. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell.
<b>Storage</b>	Store away from incompatible materials. Store in a well-ventilated place. Keep cool.
<b>Disposal</b>	Dispose of waste and residues in accordance with local authority requirements.
<b>WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)</b>	None known
<b>WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)</b>	None known
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	Not applicable.

---

### 3. Composition/Information on Ingredients

---

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy		64742-70-7	43
Stoddard solvent		8052-41-3	30

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

---

### 4. First Aid Measures

---

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Exposed individuals may experience eye tearing, redness and discomfort. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

---

### 5. Fire Fighting Measures

---

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

---

### 6. Accidental Release Measures

---

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Stop the flow of material, if this is without risk.  Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
<b>Environmental precautions</b>	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

---

### 7. Handling and Storage

---

<b>Precautions for safe handling</b>	Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use care in handling/storage. Avoid contact with eyes, skin and clothing.
--------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 8. Exposure Controls/Personal Protection

### Occupational exposure limits

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Stoddard solvent (CAS 8052-41-3)	TWA	572 mg/m3	
		100 ppm	

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Stoddard solvent (CAS 8052-41-3)	STEL	580 mg/m3
	TWA	290 mg/m3

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
	TWA	100 ppm	

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm

#### Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Stoddard solvent (CAS 8052-41-3)	TWA	525 mg/m3	
		100 ppm	

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	PEL	5 mg/m3	Mist.
	PEL	2900 mg/m3	
Stoddard solvent (CAS 8052-41-3)		500 ppm	

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
	TWA	100 ppm	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
	TWA	5 mg/m <sup>3</sup>	Mist.
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m <sup>3</sup>	
	TWA	350 mg/m <sup>3</sup>	

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines****Canada - Alberta OELs: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**Canada - Quebec OELs: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**US. NIOSH: Pocket Guide to Chemical Hazards**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Impervious gloves. Confirm with reputable supplier first.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## 9. Physical and Chemical Properties

---

<b>Appearance</b>	Liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid
<b>Color</b>	Dark blue / Green
<b>Odor</b>	Petroleum
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	> 543.2 °F (> 284 °C)
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	0.86 @ 15°C
<b>Partition coefficient (n-octanol/water)</b>	Not available.

<b>Flash point</b>	130.1 °F (54.5 °C) Pensky-Martens Closed Cup ASTM-D-93
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	27.6 cSt @ 40°C

---

## 10. Stability and Reactivity

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

---

## 11. Toxicological Information

---

<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Information on likely routes of exposure</b>	
<b>Ingestion</b>	May cause stomach distress, nausea or vomiting.
<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes eye irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Exposed individuals may experience eye tearing, redness and discomfort. Skin irritation. May cause redness and pain.

### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA > 5.5 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA > 4 mg/L, 4 Hours, ECHA > 3.9 mg/L, 4 Hours, ECHA 2.2 mg/L, 4 Hours, ECHA

Components	Species	Test Results
Oral LD50	Rat	> 5000 mg/kg, ECHA > 2000 mg/kg, ECHA 5000 mg/kg, ECHA
Stoddard solvent (CAS 8052-41-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 3000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5500 mg/m3
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes eye irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not available.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Contains < 3% (w/w) DMSO-extract	
<b>ACGIH Carcinogens</b>		
Acetic acid ethenyl ester (CAS 108-05-4)		A3 Confirmed animal carcinogen with unknown relevance to humans.
Benzene, ethyl- (CAS 100-41-4)		A3 Confirmed animal carcinogen with unknown relevance to humans.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		A2 Suspected human carcinogen.
<b>Canada - Manitoba OELs: carcinogenicity</b>		
ETHYL BENZENE (CAS 100-41-4)		Confirmed animal carcinogen with unknown relevance to humans.
MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, POORLY AND MILDLY REFINED (CAS 64742-70-7)		Suspected human carcinogen.
VINYL ACETATE (CAS 108-05-4)		Confirmed animal carcinogen with unknown relevance to humans.
<b>Canada - Quebec OELs: Carcinogen category</b>		
Acetic acid ethenyl ester (CAS 108-05-4)		Detected carcinogenic effect in animals.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Acetic acid ethenyl ester (CAS 108-05-4)		Volume 63 - 2B Possibly carcinogenic to humans.
Benzene, ethyl- (CAS 100-41-4)		Volume 77 - 2B Possibly carcinogenic to humans.
Stoddard solvent (CAS 8052-41-3)		Volume 47 - 3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)		Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.
<b>US - California Proposition 65 - CRT: Listed date/Carcinogenic substance</b>		
Benzene, ethyl- (CAS 100-41-4)		
<b>US NTP Report on Carcinogens: Known carcinogen</b>		
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		Known To Be Human Carcinogen.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
Not listed.		
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	

<b>Teratogenicity</b>	Not available.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

---

## 12. Ecological Information

---

<b>Ecotoxicity</b>	Not available.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	No data available.
<b>Mobility in general</b>	Not available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## 13. Disposal Considerations

---

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

---

## 14. Transport Information

---

**Transport of Dangerous Goods (TDG) Proof of Classification** In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

### U.S. Department of Transportation (DOT)

**Basic shipping requirements:**

<b>UN number</b>	UN1268
<b>Proper shipping name</b>	Petroleum distillates, n.o.s.
<b>Hazard class</b>	3
<b>Packing group</b>	III
<b>Special provisions</b>	144, B1, IB3, T4, TP1, TP29
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	203
<b>Packaging bulk</b>	242

### Transportation of Dangerous Goods (TDG - Canada)

**Basic shipping requirements:**

<b>UN number</b>	UN1268
<b>Proper shipping name</b>	PETROLEUM DISTILLATES, N.O.S.
<b>Hazard class</b>	3
<b>Packing group</b>	III
<b>Special provisions</b>	91, 92, 150

DOT






---

## 15. Regulatory Information

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada DSL Challenge Substances: Listed substance**

Acetic acid ethenyl ester (CAS 108-05-4) Listed.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Acetic acid ethenyl ester (CAS 108-05-4) 1 TONNES

Stoddard solvent (CAS 8052-41-3) 1 TONNES

Xylene (CAS 1330-20-7) 1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Not regulated.

**WHMIS 2015 Exemptions** Not applicable

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetic acid ethenyl ester (CAS 108-05-4) Listed.

Benzene, ethyl- (CAS 100-41-4) Listed.

Xylene (CAS 1330-20-7) Listed.

**US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity**

Acetic acid ethenyl ester (CAS 108-05-4) 5000 LBS

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**  
Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Acetic acid ethenyl ester (CAS 108-05-4)

Benzene, ethyl- (CAS 100-41-4)

Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Acetic acid ethenyl ester (CAS 108-05-4)

**US state regulations**

**US - California Hazardous Substances (Director's): Listed substance**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Listed.

Acetic acid ethenyl ester (CAS 108-05-4) Listed.



Benzene, ethyl- (CAS 100-41-4) Listed.  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Acetic acid ethenyl ester (CAS 108-05-4)  
Benzene, ethyl- (CAS 100-41-4)  
Xylene (CAS 1330-20-7)

**US - Louisiana Spill Reporting: Listed substance**

Acetic acid ethenyl ester (CAS 108-05-4) Listed.  
Benzene, ethyl- (CAS 100-41-4) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Michigan Critical Materials Register: Parameter number**

Xylene (CAS 1330-20-7) XYLENE (ALL ISOMERS)

**US - Minnesota Haz Subs: Listed substance**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Listed.  
Acetic acid ethenyl ester (CAS 108-05-4) Listed.  
Benzene, ethyl- (CAS 100-41-4) Listed.  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - New Jersey RTK - Substances: Listed substance**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8)  
Acetic acid ethenyl ester (CAS 108-05-4)  
Benzene, ethyl- (CAS 100-41-4)  
Stoddard solvent (CAS 8052-41-3)  
Xylene (CAS 1330-20-7)

**US - North Carolina Toxic Air Pollutants: Listed substance**

Xylene (CAS 1330-20-7)

**US - Texas Effects Screening Levels: Listed substance**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8) Listed.  
Acetic acid ethenyl ester (CAS 108-05-4) Listed.  
Benzene, ethyl- (CAS 100-41-4) Listed.  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Benzene, ethyl- (CAS 100-41-4)

**US. Massachusetts RTK - Substance List**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8)  
Acetic acid ethenyl ester (CAS 108-05-4)  
Benzene, ethyl- (CAS 100-41-4)  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)  
Stoddard solvent (CAS 8052-41-3)  
Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Acetic acid ethenyl ester (CAS 108-05-4)  
Benzene, ethyl- (CAS 100-41-4)  
Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8)  
Acetic acid ethenyl ester (CAS 108-05-4)  
Benzene, ethyl- (CAS 100-41-4)  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)  
Stoddard solvent (CAS 8052-41-3)  
Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

(2-Methoxymethylethoxy) propanol (CAS 34590-94-8)  
Acetic acid ethenyl ester (CAS 108-05-4)  
Benzene, ethyl- (CAS 100-41-4)  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)  
Stoddard solvent (CAS 8052-41-3)  
Xylene (CAS 1330-20-7)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Benzene, ethyl- (CAS 100-41-4)

Listed: June 11, 2004

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other Information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	* 2
<b>FLAMMABILITY</b>	2
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

22-January-2018

**Version #**

02

**Effective date**

22-January-2018

**Prepared by**

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

**Other information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.