



SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Hydrate Breaker
Other means of identification	Not available
Recommended use	Hydrate breaker
Recommended restrictions	None known.
Manufacturer information	Irving Blending & Packaging PO Box 1169 Saint John, NB E2L 4E6 CA Phone: 1.800.574.5823 Emergency Phone: 1.506.648.3060
Supplier	See above.

2. Hazards Identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 4
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, single exposure	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May damage fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection.
Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Do not breathe mist or vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Response

In case of fire: Use appropriate media to extinguish.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Specific treatment (see information on this label).

Storage	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Methanol		67-56-1	51
Isopropanol		67-63-0	40
1,2-Ethandiol		107-21-1	6
Acetone		67-64-1	2
Ethanol, 2,2"-oxybis-		111-46-6	<1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. Treat patient symptomatically.
General information	Take off all contaminated clothing immediately. Immediate medical attention is required. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Keep away from sources of ignition. No smoking. Avoid contact with eyes and skin. Keep out of reach of children. Wear rubber gloves and safety glasses with side shields.

5. Fire Fighting Measures

Suitable extinguishing media	Water fog. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Avoid breathing vapors or mists of this product. Do not taste or swallow. Avoid contact with eyes, skin and clothing. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Use only outdoors or in a well-ventilated area. Avoid prolonged exposure. Wash thoroughly after handling. Keep container tightly closed. Use good industrial hygiene practices in handling this material.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Do not store at temperatures above 120°F (49°C). Keep away from heat, sparks, and flame. Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Isopropanol (CAS 67-63-0)	PEL	980 mg/m ³ 400 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m ³ 200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2-Ethanediol (CAS 107-21-1)	Ceiling	100 mg/m ³	Aerosol.
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
Methanol (CAS 67-56-1)	STEL	325 mg/m3
		250 ppm
	TWA	260 mg/m3
		200 ppm

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Ethanol, 2,2''-oxybis- (CAS 111-46-6)	TWA	10 mg/m3

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*
Isopropanol (CAS 67-63-0)	40 mg/L	Acetone	Urine	*
Methanol (CAS 67-56-1)	15 mg/L	Methanol	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines See above

Canada - Alberta OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Rubber gloves. Confirm with a reputable supplier first.

Other Wear suitable protective clothing. Use of an impervious apron is recommended. As required by employer code.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Thermal hazards Not applicable.

General hygiene considerations Observe any medical surveillance requirements. When using do not smoke. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Clear
Physical state	Liquid.
Form	Liquid.
Color	Colorless
Odor	Strong
Odor threshold	Not available.
pH	8
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	< -76 °F (< -60 °C)
Specific gravity	0.8167 @ 15°C
Partition coefficient (n-octanol/water)	Not available.
Flash point	51.8 °F (11.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.8167 @ 15°C
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
Incompatible materials	Caustics. Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure	Eye, Skin contact, Skin absorption, Inhalation, Ingestion.
Information on likely routes of exposure	
Ingestion	Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Inhalation	Harmful if inhaled. May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Harmful if inhaled. Harmful if swallowed. Narcotic effects. Although animal toxicity values do not meet criteria, ethylene glycol is toxic to humans. There are numerous human case reports of toxicity and death published in the literature.

Components	Species	Test Results
1,2-Ethanediol (CAS 107-21-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	9500 mg/kg
<i>Inhalation</i>		
LC50	Rat	2725 mg/m ³ , 4 hr
<i>Oral</i>		
LD50	Cat	1650 mg/kg
	Dog	5500 mg/kg
	Guinea pig	6600 mg/kg
	Human	1110 - 1665 mg/kg
	Mouse	7500 mg/kg
	Rabbit	5000 mg/kg
	Rat	5890 mg/kg
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15800 mg/kg 20 ml/kg
<i>Inhalation</i>		
LC50	Mouse	44000 mg/m ³ /4H
	Rat	76 mg/L, 4 Hours 50.1 mg/L, 8 Hours 39 mg/l/4h
<i>Oral</i>		
LD50	Human	2857 mg/kg
	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Ethanol, 2,2'-oxybis- (CAS 111-46-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	11890 mg/kg
<i>Oral</i>		
LD50	Cat	3300 mg/kg
	Dog	9000 mg/kg
	Guinea pig	8700 mg/kg
	Human	1000 mg/kg
	Mouse	23700 mg/kg
		13.3 g/kg
	Rat	12565 mg/kg

Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12800 mg/kg
<i>Inhalation</i>		
LC50	Rat	16970 mg/l/4h
<i>Oral</i>		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
	Rabbit	5030 mg/kg
	Rat	4396 mg/kg
Methanol (CAS 67-56-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15800 - 20000 mg/kg
	Rat	> 450000 mg/kg
<i>Inhalation</i>		
LC50	Cat	85.4 mg/l/4h
		43.7 mg/L, 6 Hours
	Rat	64000 ppm, 4 Hours
		87.5 mg/L, 6 Hours
		83.2 - 128.8 mg/l/4h
<i>Oral</i>		
LD50	Dog	8000 mg/kg
	Human	143 - 300 mg/kg
	Monkey	3000 mg/kg
		2000 mg/kg
	Mouse	7300 mg/kg
	Rabbit	14200 - 14400 mg/kg
	Rat	790 - 13000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.	
Carcinogenicity	See below.	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
	Not listed.	
Reproductive toxicity	May damage fertility or the unborn child.	

Teratogenicity	In rats and mice exposed to ethylene glycol, embryotoxic (late resorptions), fetotoxic (reduced fetal body weight) and teratogenic (external, soft tissue and skeletal defects) effects were observed at relatively high oral doses that caused no or minimal maternal toxicity.
	Methanol has produced teratogenic effects in mice exposed by inhalation to high concentrations that did not produce significant maternal toxicity.
Specific target organ toxicity - single exposure	Causes damage to organs. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data			
Components		Species	Test Results
1,2-Ethenediol (CAS 107-21-1)			
Crustacea	EC50	Daphnia	46300 mg/L, 48 Hours
Aquatic			
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	8050 mg/L, 96 hours
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	10294 - 17704 mg/L, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	4740 - 6330 mg/L, 96 hours
Ethanol, 2,2"-oxybis- (CAS 111-46-6)			
Crustacea	EC50	Daphnia	84000 mg/L, 48 Hours
Aquatic			
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>)	> 32000 mg/L, 96 hours
Isopropanol (CAS 67-63-0)			
Algae	IC50	Algae	1000 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/L, 96 hours
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	> 10000 mg/L, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	> 100 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

U.S. Department of Transportation (DOT)**Basic shipping requirements:**

UN number	UN1993
Proper shipping name	Flammable liquids, n.o.s.
Technical name	Methanol
Technical name	Isopropanol
Hazard class	3
Packing group	II
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150

Transportation of Dangerous Goods (TDG - Canada)**Basic shipping requirements:**

UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	Methanol
Technical name	Isopropanol
Hazard class	3
Packing group	II
Special provisions	16, 150

DOT**TDG**

15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Listed substance/Identification Number

Isopropanol (CAS 67-63-0)	Listed.
Methanol (CAS 67-56-1)	Listed.

Canada Priority Substances List (Second List): Listed substance

1,2-Ethanediol (CAS 107-21-1)	Listed.
-------------------------------	---------

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Acetone (CAS 67-64-1)	Class B
-----------------------	---------

WHMIS 2015 Exemptions Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,2-Ethanediol (CAS 107-21-1)	Listed.
Acetone (CAS 67-64-1)	Listed.
Isopropanol (CAS 67-63-0)	Listed.
Methanol (CAS 67-56-1)	Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance	No
---	----

SARA 311/312 Hazardous chemical	No
--	----

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	51
Isopropanol	67-63-0	40
1,2-Ethanediol	107-21-1	6

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

1,2-Ethanediol (CAS 107-21-1)
Methanol (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)	Not regulated.
---------------------------------------	----------------

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
-----------------------	------

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35 %WV
-----------------------	--------

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
-----------------------	------

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1)	Low priority
Isopropanol (CAS 67-63-0)	Low priority

Food and Drug Administration (FDA)	Not regulated.
---	----------------

US state regulations**US - California Hazardous Substances (Director's): Listed substance**

1,2-Ethanediol (CAS 107-21-1)	Listed.
Acetone (CAS 67-64-1)	Listed.
Isopropanol (CAS 67-63-0)	Listed.
Methanol (CAS 67-56-1)	Listed.

US - Illinois Chemical Safety Act: Listed substance

1,2-Ethanediol (CAS 107-21-1)
Acetone (CAS 67-64-1)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)

US - Louisiana Spill Reporting: Listed substance

1,2-Ethanediol (CAS 107-21-1)	Listed.
Acetone (CAS 67-64-1)	Listed.
Isopropanol (CAS 67-63-0)	Listed.
Methanol (CAS 67-56-1)	Listed.

US - Minnesota Haz Subs: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Acetone (CAS 67-64-1) Listed.
Ethanol, 2,2"-oxybis- (CAS 111-46-6) Listed.
Isopropanol (CAS 67-63-0) Listed.
Methanol (CAS 67-56-1) Listed.

US - New Jersey RTK - Substances: Listed substance

1,2-Ethanediol (CAS 107-21-1)
Acetone (CAS 67-64-1)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)

US - Texas Effects Screening Levels: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Acetone (CAS 67-64-1) Listed.
Ethanol, 2,2"-oxybis- (CAS 111-46-6) Listed.
Isopropanol (CAS 67-63-0) Listed.
Methanol (CAS 67-56-1) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

1,2-Ethanediol (CAS 107-21-1)

US. Massachusetts RTK - Substance List

1,2-Ethanediol (CAS 107-21-1)
Acetone (CAS 67-64-1)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)

US. New Jersey Worker and Community Right-to-Know Act

1,2-Ethanediol (CAS 107-21-1)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)

US. Pennsylvania RTK - Hazardous Substances

1,2-Ethanediol (CAS 107-21-1)
Acetone (CAS 67-64-1)
Ethanol, 2,2"-oxybis- (CAS 111-46-6)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)

US. Rhode Island RTK

1,2-Ethanediol (CAS 107-21-1)
Acetone (CAS 67-64-1)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document. The information in the sheet was written based on the best knowledge and experience currently available.

Issue date

07-April-2016

Version #

01

Effective date

07-April-2016

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.