



SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Cobra UTF - US only		
Other means of identification	Not available		
Recommended use	Lubricant		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	Coastal Blending & Packaging		
Address	PO Box 1169 Saint John, NB E2L 4E6 Canada		
Telephone	Phone:	1.800.574.5823	
E-mail	Not available.		
Emergency phone number	Emergency Phone:	1.506.648.3060	

2. Hazards Identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Not available.
Disposal	Dispose of container in accordance with local, regional, national and international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on Ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Base Oil		Trade Secret	65-85*
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	5-10*
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	0.1-1*
Mineral Oil		Mixture	1-5*
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy		64742-70-7	10-30*

Composition comments US GHS: The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
General information	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Carbon dioxide. Water fog. Foam. Dry chemical powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe with absorbent material and discard. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling	Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

U.S. - OSHA

Components	Type	Value
Mineral oil (CAS Mixture)	TWA	5 mg/m ³

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m ³	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m ³	Mist.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	PEL	5 mg/m ³	Mist.

ACGIH Components			
Components	Type	Value	
Mineral oil (CAS Mixture)	TWA	5 mg/m3	
US. ACGIH Threshold Limit Values			
Components	Type	Value	Form
Base Oil (CAS Trade Secret)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2) Can be absorbed through the skin.
 Phenol (CAS 108-95-2) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

1-Butanol (CAS 71-36-3) Can be absorbed through the skin.
 Phenol (CAS 108-95-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Phenol (CAS 108-95-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Impervious gloves. Confirm with reputable supplier first.

Other Wear appropriate chemical resistant clothing. Wear suitable protective clothing. Use of an impervious apron is recommended. As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

Wash hands before breaks and immediately after handling the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	Characteristic
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-38.2 °F (-39 °C)
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	408.2 °F (209.0 °C) Pensky-Martens Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.8612 @ 15°C
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	9.9 cSt @ 100°C 60.5 cSt @ 40°C

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause stomach distress, nausea or vomiting.

Symptoms related to the physical, chemical and toxicological characteristics There are no hazards associated with this product in normal use. Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not classified.

Components	Species	Test Results
Base Oil (CAS Trade Secret)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 4480 mg/kg
	Rat	> 2000 mg/kg
<i>Oral</i>		
LD50	Rat	> 2000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA
		> 5.5 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.2 mg/L, 4 Hours, ECHA
		> 4 mg/L, 4 Hours, ECHA
		> 3.9 mg/L, 4 Hours, ECHA
		2.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
		> 2000 mg/kg, ECHA
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg, ECHA
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA
		> 5.5 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.2 mg/L, 4 Hours, ECHA
		> 4 mg/L, 4 Hours, ECHA
		> 3.9 mg/L, 4 Hours, ECHA
		2.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
		> 2000 mg/kg, ECHA
		5000 mg/kg, ECHA
Mineral Oil (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 2.2 mg/L, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA
		> 5.5 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.2 mg/L, 4 Hours, ECHA
		> 4 mg/L, 4 Hours, ECHA
		> 3.9 mg/L, 4 Hours, ECHA
		2.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
		> 2000 mg/kg, ECHA
		5000 mg/kg, ECHA
Skin corrosion/irritation	Not available.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Not available.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	Not available.	
Germ cell mutagenicity	Not available.	
Carcinogenicity	See below. Contains < 3% (w/w) DMSO-extract	
ACGIH Carcinogens		
Base Oil (CAS Trade Secret)		A2 Suspected human carcinogen.
Benzene (CAS 71-43-2)		A4 Not classifiable as a human carcinogen.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		A1 Confirmed human carcinogen.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		A4 Not classifiable as a human carcinogen.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		A2 Suspected human carcinogen.
Phenol (CAS 108-95-2)		A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity		
Benzene (CAS 71-43-2)		Volume 29, Supplement 7, Volume 100F 1 Carcinogenic to humans.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.
Phenol (CAS 108-95-2)		Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.
US - California Proposition 65 - CRT: Listed date/Carcinogenic substance		
Benzene (CAS 71-43-2)		

US. National Toxicology Program (NTP) Report on Carcinogens

Base Oil (CAS Trade Secret)	Known To Be Human Carcinogen.
Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Known To Be Human Carcinogen.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene (CAS 71-43-2)	Cancer
-----------------------	--------

Reproductive toxicity	Not available.
Specific target organ toxicity - single exposure	Not available.
Specific target organ toxicity - repeated exposure	Not available.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Not available.
Further information	Not available.

12. Ecological Information

Ecotoxicity	See below
--------------------	-----------

Ecotoxicological data

Components	Species	Test Results
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Mobility in general	Not available.
Other adverse effects	Not available.

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information**U.S. Department of Transportation (DOT)**

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

US federal regulations	This product is NOT known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
-------------------------------	--

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1-Butanol (CAS 71-36-3)	Listed.
1-Propanol, 2-methyl- (CAS 78-83-1)	Listed.
Benzene (CAS 71-43-2)	Listed.

Phenol (CAS 108-95-2)	Listed.
US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity	
Phenol (CAS 108-95-2)	1000 LBS
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Benzene (CAS 71-43-2)	Cancer Central nervous system Blood Aspiration Skin Eye respiratory tract irritation Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
SARA 302 Extremely hazardous substance	No
SARA 311/312 Hazardous chemical	No
SARA 313 (TRI reporting)	Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Benzene (CAS 71-43-2)
Phenol (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

1-Butanol (CAS 71-36-3)	Low priority
1-Propanol, 2-methyl- (CAS 78-83-1)	Low priority
Phenol (CAS 108-95-2)	Low priority

Food and Drug Administration (FDA) Not regulated.

US state regulations See below

US - Illinois Chemical Safety Act: Listed substance

1-Butanol (CAS 71-36-3)
1-Propanol, 2-methyl- (CAS 78-83-1)
Benzene (CAS 71-43-2)
Phenol (CAS 108-95-2)

US - Louisiana Spill Reporting: Listed substance

1-Butanol (CAS 71-36-3)	Listed.
1-Propanol, 2-methyl- (CAS 78-83-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Phenol (CAS 108-95-2)	Listed.

US - Michigan Critical Materials Register: Parameter number

Benzene (CAS 71-43-2)	BENZENE
-----------------------	---------

US - Minnesota Haz Subs: Listed substance

1-Butanol (CAS 71-36-3)	N-BUTYL ALCOHOL
1-Propanol, 2-methyl- (CAS 78-83-1)	ISOBUTYL ALCOHOL
Benzene (CAS 71-43-2)	BENZENE
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	OIL MIST, MINERAL
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	OIL MIST, MINERAL
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	OIL MIST, MINERAL
Phenol (CAS 108-95-2)	PHENOL

US - New Jersey RTK - Substances: Listed substance

1-Butanol (CAS 71-36-3)

1-Propanol, 2-methyl- (CAS 78-83-1)
Benzene (CAS 71-43-2)
Phenol (CAS 108-95-2)

US - North Carolina Toxic Air Pollutants: Listed substance

Benzene (CAS 71-43-2)
Phenol (CAS 108-95-2)

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Benzene (CAS 71-43-2)

US - Washington Chemical of High Concern to Children: Listed substance

Benzene (CAS 71-43-2)
Phenol (CAS 108-95-2)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

1-Butanol (CAS 71-36-3)
1-Propanol, 2-methyl- (CAS 78-83-1)
Benzene (CAS 71-43-2)
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Phenol (CAS 108-95-2)

US. New Jersey Worker and Community Right-to-Know Act

1-Butanol (CAS 71-36-3)
Benzene (CAS 71-43-2)
Phenol (CAS 108-95-2)

US. Pennsylvania RTK - Hazardous Substances

1-Butanol (CAS 71-36-3)
1-Propanol, 2-methyl- (CAS 78-83-1)
Benzene (CAS 71-43-2)
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Phenol (CAS 108-95-2)

US. Pennsylvania Worker and Community Right-to-Know Law

1-Butanol (CAS 71-36-3)
1-Propanol, 2-methyl- (CAS 78-83-1)
Benzene (CAS 71-43-2)
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Phenol (CAS 108-95-2)

US. Rhode Island RTK

1-Butanol (CAS 71-36-3)
1-Propanol, 2-methyl- (CAS 78-83-1)
Benzene (CAS 71-43-2)
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Phenol (CAS 108-95-2)

US. California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Country(s) or region

Inventory name

On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory


Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/	1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

10-June-2019

Version

01

Further information

Not available.

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021